

-GENESIS-

General Purpose Security & Control Cable

Part Number: 1206

22 AWG 6 Stranded Conductors Shielded

Ratings CM, CL2, Sunlight Resistant

Approvals ETL Listed

Construction

Conductor 22 AWG 7 Strand Bare Copper

Conductor Count 6

Insulation Polypropylene (0.006" nom.)

Insulation Colors Black, Red, White, Green, Brown, Blue

Lay Length 3" nom.

Shielding Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain

Rip Cord Yes

Jacket PVC (0.015 " nom.)

Overall Diameter 0.166" nom.

Print Legend GENESIS P/N 1206 6C22 SHIELDED 3038058 (ETL) CL2 OR CM C(ETL)US SUN RES
(RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Operating Voltage 300 Volts max.

DC Resistance 16.9 Ohms/1000' at 20°C

Capacitance 18.5 pF/ft. nom.

Impedance 59 Ohms nom.

Temperature -20°C to 60°C

Flame Rating UL 1685 Vertical Tray

RoHS Compliant Yes

Country of Origin USA